

SC-95TN

Ref: LDASC95TNS01

EN 54-24



The SC-95TN is a high performance 24 W ceiling coaxial 2 ways speaker. Its broad frequency range, low distortion, and high sound pressure level ensures the delivery of intelligible voice and excellent sound. The stylish low profile and white color design allows it to blend easily with most applications, such as hotels, shopping malls, conference rooms and exhibition halls.

This coaxial ceiling loudspeaker is EN 54-24 certified, what ensures that, in the event of a fire, damage to the loudspeaker does not result in failure of the loudspeaker circuit which is connected.

Features of the SC-95TN :

- It is EN 54-24 certified
- Intelligible voice and excellent sound reproduction
- Easy blending with any indoor decorations
- Robust metal case with fireproof dome
- Simple power setting and wiring

Technical Specifications:

Model	SC-95TN
Reference	LDASC95TNS01
Max power	36 W
Rated power	24 W
Power taps @ 100V	24 W / 12 W / 6 W / 3 W / 4 Ω
SPL at 2 W / 1 W (100 Hz – 10 kHz, 1 m)	103 dB / 91 dB
SPL at 24 W / 1 W (100 Hz – 10 kHz, 4 m)	91 dB / 79 dB
Frequency response (- 10 dB)	120 Hz – 20 kHz
Rated input voltage	100 V / 70 V
Rated impedance	0.42 kΩ / 0.83 kΩ / 1.67 kΩ / 3.33 kΩ / 4 Ω
Connection	Fire-resistant cable
Dimensions	Φ 226 mm × 129 mm
Hole cut-out size	Φ195 mm
Weight	2.25 kg
Colour	White (RAL 9003) / Red (RAL 3000)
IP protection grade	IP21 (A type according to EN54-24)
Speaker size	6.5"
Operating temperature	-25°C to +55°C
Storage temperature	-40°C to +70°C
Relative humidity	up to 95%