

TCH-12



The LDA-TCH12T touch control panel uses a standard 4-wire resistive touch panel, which allows up to a total of 32 command code with complete user programmable software. User friendly Software which allows customized programming such as macros setting, feedback events, control commands, etc. Another characteristic is the panel button layout and design, it can be easily customized and print out accordingly with icons or clear text buttons

Features:

- Feature with automatic backlight fade out
- Macro definitions setting can be assign for every single button up to 16 difference order
- Default 3x4 matrix of 12 touch buttons
- With 1 x RS-232 or 1 x RS-485 selectable and 1 x RS-232
- Ultra low power consumption
- Designed for any professional control system requiring multiple lighting/dimming or environmental control.

CARACTERÍSTICAS TÉCNICAS	
INPUT VOLTAGE	12V-DC, 350mA
BACK LIGHT	With white LED light guide plate
COMMUNICATION	RS-232 or RS485 (*Selectable)
STANDARD	1 x RS-232 or 1x RS-485
CONFIGURABLE COM PORT	(7 or 8 Data Bit and 1 or 2 Stop Bit)
TOTAL NUMBER OF COMMAND SET ALLOW	32
STANDBY CURRENT	35mA
OPERATION CURRENT	65mA
HOUSING	ABS
DIMENSIONS / WEIGHT	88 x 88 x 16 mm / 75g
ACCESSORIES	AC-DC Power Adaptor 12V-DC, 350mA 1 x 2 Pin, 2 x 3 Pin Terminal Block